

## HP Series 3 Pro 23.8 inch FHD Monitor - 324pb







 $\underline{\mathsf{Series}} \, o \,$ 

## Specifications

## **All Specs**

Aspect ratio

16:9

Audio port

1 x 3.5 mm Audio Jack (Audio In)

Backlight lamp life minimum (to

half brightness)

30,000 hours

Backlight type

Edge-lit

Base area footprint (metric)

23 x 19 cm

Bezel

3-sided borderless

Brightness

250 nits

Camera

No integrated camera

Certifications and compliances

BIS; CB(62368-1); TUV Rheinland

Color

Black

Color gamut

72% NTSC

Contrast ratio

1200:1

Country of origin

India(ACJ)

Curvature

Flat

Detachable stand

Yes

Dimensions (W x D x H)

54.1 x 4.7 x 32.6 cm (without stand)

Dimensions With Stand (W x D x

H)

54.1 x 19 x 41.6 cm

Display area (metric)

52.7 x 29.65 cm

Display colors

Up to 16.7 million colors supported

Display contrast ratio (dynamic)

1,000,000:1

Display features

Tilt

Display scan frequency (horizontal)

30-86 kHz

Display scan frequency

(vertical)

50-75 Hz

Display size (diagonal) 60.5 cm (23.8")

DisplayPort™ 1.2

Ecolabels TCO Certified

End of Life CO2e (kg) 2

Energy star certified ENERGY STAR® certified

Hardness 3H

Haze 25%

HDCP Yes, DisplayPort™ and HDMI

HDMI 1.4

Horizontal viewing angle 178°

Low blue light TÜV certified

Manufacturer Warranty HP three-year limited warranty

Material Type for item FERT

Native resolution FHD (1920 x 1080)

Non-Operating Humidity Range 5-90 %

Non-operating temperature -

Celsius

-20 to 60°C

Operating altitude Up to 5,000 m  $\,$ 

Operating humidity range 5 to 90% RH

Operating temperature range 32 to 122°F

Package dimensions (W x D x H)  $59.5 \times 12.5 \times 39 \text{ cm}$ 

Package weight 4.5 kg

Pallet (layers) 5

Pallet dimensions (W x D x H)  $109.5 \times 109.5 \times 207.5 \text{ cm}$ 

Pallet weight 372 kg

Panel bit depth 8 bit (6 bit + 2 FRC)

Panel technology IPS; LCD

Physical security Security lock-ready

**Pixel pitch** 0.2745 x 0.2745 mm

Pixels per inch (ppi) 93 ppi

Power 100 - 240 VAC 50/60 Hz

Power consumption 36 W (maximum), 18 W (typical), 0.5 W (standby)

Power supply type External

Product color Black

Production CO2e (kg) 156

Products per pallet 80

Products per pallet layer 16

Refresh rate (maximum) 75 Hz

Registration required No

Resolution (maximum) FHD (1920  $\times$  1080 @ 75 Hz)

Resolutions supported

640 x 480 @ 60 Hz; 720 x 400 @ 70 Hz; 800 x 600 @ 60 Hz; 1024 x 768 @ 60 Hz; 1280 x 720 @ 60 Hz; 1280 x 1024 @ 60 Hz; 1440 x 900
@ 60 Hz; 1600 x 900 @ 60 Hz; 1680 x 1050 @ 60 Hz; 1920 x 1080 @ 60 Hz; 640 x 480 @ 75Hz (HDMI only); 800 x 600 @ 75 Hz (HDMI only); 1024 x 768 @ 75 Hz (HDMI only); 1280 x 1024 @ 75 Hz (HDMI only); 1920 x 1080 @ 50 Hz (HDMI only); 1920 x 1080 @ 75 Hz (HDMI only); 720 x 480 @ 60 Hz; 720 x 576 @ 50 Hz; 1280 x 800 @ 60 Hz

Response time (typical) 5ms GtG (with overdrive)

Screen treatment Anti-glare

Speaker output power 2 x 1.5 W

Stand color Black

Stand type Fixed height stand; Base stand; With stand

Sustainable impact specifications

Low halogen; Recycled plastic cushions; 2% post-consumer recycled plastic

Tilt -5 to +15°

Total CO2e (kg) 290

Total CO2e (kg) note

A product carbon footprint is defined as the total amount of greenhouse gases emitted directly and indirectly by a product over its lifetime. Greenhouse gas emissions are reported as global warming potential for 100-year time horizon (GWP-100) in units of CO2 equivalence. Calculations are done in accordance with ISO 14040 & ISO 14044. Individual values may not sum to total due to

rounding.

2

Transportation CO2e (kg)

UNSPSC code 43211902

UPC number 198828485618

Vertical viewing angle 178°

VESA mounting 100 x 100 mm

VGA 1VGA

 Video connectors
 HDMI; DisplayPort™-in

Viewable diagonal size 23.8" (60.47 cm)

Weight 2.9 kg (with stand); 2.64 kg (without stand)

What's in the box Monitor; HDMI cable; Warranty card; Power adapter; Quick Setup Poster; AC power cord

Logistics

UPC number 198828485618

What's in the box Monitor; HDMI cable; Warranty card; Power adapter; Quick Setup Poster; AC power cord

Base area footprint (metric) 23 x 19 cm

Package dimensions (W x D x H) 59.5 x 12.5 x 39 cm

Pallet dimensions (W  $\times$  D  $\times$  H) 109.5  $\times$  109.5  $\times$  207.5 cm

Dimensions (W x D x H) 54.1 x 4.7 x 32.6 cm (without stand)

Dimensions With Stand (W x D x

H)

54.1 x 19 x 41.6 cm

Country of origin India(ACJ)

Pallet (layers) 5

Products per pallet 80

Products per pallet layer 16

Material Type for item FERT



UNSPSC code	43211902
Package weight	4.5 kg
Pallet weight	372 kg
Weight	2.9 kg (with stand); 2.64 kg (without stand)
Specifications	
[1] All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.	
[2] DisplayPort™ 1.2 or HDMI 1.4 required to drive panel at its native resolution. The video card of the connected PC must be capable of supporting 1920 x 1080 and include one DisplayPort™, one HDMI or one VGA outputs to drive the monitor at the Preferred Mode.	
[3] Number of colors through A-FRC technology.	
[4] Service parts obtained after purchase may not be Low Halogen.	
[5] Plastic cushions are made from >90% recycled plastic.	
[6] Recycled plastic content percentage is based on the definition set in the IEEE 1680.1-2018 standard.	
[7] Included cables may vary by country.	
[8] Lock sold separately.	
Legal disclaimer	
Product image may differ from actual product	
[3] FHD content is required to view FHD images.	
[4] This product has been verified to meet ENERGY STAR® requirements.	
DisplayPort <sup>™</sup> and the DisplayPort <sup>™</sup> logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. ENERGY STAR® is a registered mark owned by the U.S. government.	